

# **EVO-SALTAWAY<sup>®</sup>**

## **ECO FRIENDLY EFFLORESCENCE REMOVER**

### **DESCRIPTION:**

**EVO-SALTAWAY- an industrial strength efflorescence (SALT) remover specially formulated for industrial, commercial and residential use on concrete or masonry surfaces.**

Non-flammable, non-carcinogenic, biodegradable and non-hazardous formulation with no solvents or other aggressive chemicals, allows effective removal of efflorescence without harmful effects for the environment.

### **APPLICATION FIELDS:**

- General removal of efflorescence.
- Cleaning of historical monuments, public buildings and new or old constructions affected by efflorescence.
- Masonry, brick, block structures, walls, floors suffering efflorescence.

### **ADVANTAGES:**

- It does not attack the surface treated.
- Dissolves efflorescence deposits, allowing removal.
- Safe for users and adjacent areas, it does not require special protection equipments.
- Non-flammable. Environmental friendly. Saves costs of hazardous classified materials for transportation.
- Replaces **aggressive** acid and basic cleaners.

### **SURFACE PREPARATION:**

#### **Preparation of the surface**

Remove all loose material and remove excessive build-up of efflorescence.

**If required use EVO-POWER CLEAN**

### **APPLICATION:**

**APPLY EVO-SALTAWAY** by pump spray ensuring a uniform and homogeneous coverage.

**Apply until “FOAM” begins to appear. Foam only appears when efflorescence is present. Stubborn deposits may require mechanical agitation to remove,**

Wait 5 minutes, re-apply as required, mechanically agitate and high pressure clean to remove efflorescence.

Keep applying **EVO-SALTAWAY** to areas where foam appears and continue to apply until foam no longer forms.

Remove by rinsing area thoroughly with water and allow to dry as much as possible.

**APPLY EVO-SEAL to prevent further salt formation.**

**Protect all other surfaces other than area to be treated. If other areas a subjected to the product rinse immediately.**

### **CLEANING:**

Tools and equipments should be cleaned with water directly after use.

### **PACKAGING :**

**EVO-SALTAWAY** is supplied in 5lit, 20lit and 200lit containers.

### **STORAGE:**

12 month in its original unopened containers, in a dry and covered place protected from frost, with temperatures ranging from 5 °C. To 38 °C

### **SAFETY AND HEALTH:**

**EVO-SALTAWAY** is a non-flammable product, eye and skin contact must be avoided. Use gloves and safety goggles. In case of eye contact, thoroughly clean with clean water but do not rub. In case of skin contact, wash affected areas with water and soap. If irritation persists, seek medical attention.

**TECHNICAL DATA:**

**WARRANTY:** 10 year Manufacturer

<b>Characteristics of the product –Non-Toxic-Non-Flammable</b>	
Appearance	Clear Liquid
Evaporation	Less in 1.0@ 24 °C
Specific Gravity	(H2o 1)1.0-1.2 @ 24 °C
pH --%solids	1.0 -----2%+/- 0.02%
Minimum application temperature (°C)	> 7
Solubility/Evaporation Rate	DILUTABLE-(BAC=1) same as water
Flash point/Boiling Point/Freezing Point	Non-flammable-Same as Water
Estimated consumption per treatment*	1 lit 5-7/m <sup>2</sup>

\* Depending on absorption, texture and substrate conditions as well as application method.  
Amended 24/03/2011

**MASONRY WATERPROOFING SYSTEMS PTY LTD**  
**SALES AND TECHNICAL FREECALL: 1800 539 339**

**P.O. Box 139 Riverwood NSW**

**E-mail: [info@mwsystems.com.au](mailto:info@mwsystems.com.au)**

**web: [www.mwsystems.com.au](http://www.mwsystems.com.au)**

**[www.evoproducts.com.au](http://www.evoproducts.com.au)**

